

PC4900 GUAINA DI PROTEZIONE TERMICA IN VETRO-SILICONE 200°C PER TUBI FLESSIBILI SILICON-GLASS THERMAL PROTECTION 200°C FOR FLEXIBLE HOSES



Caratteristiche tecniche:

Campo di temperatura: -40°C/+200°C (260°C di picco). Spessore parete in silicone 1 mm. Autoestinguente. Norme: 1441 VW – I – EN 45545-1 EN 45545-2+A1

Technical features:

Working temperature range: -40°C/+200°C (peaks of 260°C). Silicon wall thickness: 1 mm. Fire self-extinguish. Standards: 1441 VW – I – EN 45545-1 EN 45545-2+A1

PC5110

FASCETTA A DUE ORECCHIE ACCIAIO ZINCATO
GALVANIZED STEEL DOUBLE-HEAR CLIP



Codice-Code	Ø interno inner	Colore Colour	Tubo - Hose	
			PC4600	PC4650
PC5110-1113-Z	10	PC4900-010-R-L001	1/4"	1/4"
		PC4900-010-N-L001		
PC5110-1417-Z	14	PC4900-014-R-L001	3/8"	-
		PC4900-014-N-L001		
PC5110-1720-Z	18	PC4900-018-R-L001	1/2"	3/8"
PC5110-2023-Z	20	PC4900-020-R-L001	-	1/2"
		PC4900-020-N-L001	*1/2"	*3/8"-1/2"
PC5110-2327-Z	25	PC4900-025-R-L001	3/4"	-
PC5110-2731-Z	28	PC4900-028-R-L001	-	3/4"
PC5110-3134-Z	30	PC4900-030-R-L001	1"	-
PC5110-3740-Z	38	PC4900-038-R-L001	-	1"

PC4901 GUAINA ELASTICA DI PROTEZIONE TERMICA IN VETRO-SILICONE 260°C PER TUBI FLESSIBILI ELASTIC SILICON-GLASS THERMAL PROTECTION 260°C FOR FLEXIBLE HOSES



Caratteristiche tecniche:

Campo di temperatura: -40°C/+260°C (290°C di picco). Spessore parete in silicone 1 mm. Autoestinguente. Norme: 1441 VW – I – EN 45545-1 EN 45545-2+A1

Technical features:

Working temperature range: -40°C/+260°C (peaks of 290°C). Silicon wall thickness: 1 mm. Fire self-extinguish. Standards: 1441 VW – I – EN 45545-1 EN 45545-2+A1

PC5110

FASCETTA A DUE ORECCHIE ACCIAIO ZINCATO
GALVANIZED STEEL DOUBLE-HEAR CLIP



Codice-Code	Ø interno inner	Colore Colour	Tubo - Hose	
			PC4600	PC4650
PC5110-1113-Z	10	PC4901-10-R-L001	1/4"	1/4"
		PC4901-10-N-L001		
PC5110-1417-Z	14	PC4901-014-R-L001	3/8"	-
		PC4901-014-N-L001		
PC5110-1720-Z	16	PC4901-016-R-L001	-	3/8"
		PC4901-016-N-L001		
PC5110-2023-Z	20	PC4901-020-R-L001	1/2"	1/2"
		PC4901-020-N-L001		
PC5110-2528-Z	24	PC4901-024-R-L001	3/4"	-
		PC4901-024-N-L001		
PC5110-2528-Z	26	PC4901-026-R-L001	-	3/4"
		PC4901-026-N-L001		
PC5110-3134-Z	30	PC4901-030-R-L001	1"	-
		PC4901-030-N-L001		
PC5110-3437-Z	35	PC4901-035-R-L001	-	1"
		PC4901-035-N-L001		